

AMENDMENTS TO THE CLAIMS

1. (Withdrawn, Previously amended) A transfer member comprising:
 - a) a body having a carbon-fiber reinforced composite material, said body having a top surface and a bottom surface;
 - b) a metal film covering the top and bottom surfaces of the composite body, said film forming a reflective surface;
 - c) a glass fiber epoxy resin forming a layer on the metal film covering the top surface and the bottom surface of the body; and
 - d) at least one electroconductive polymer part electrically connected to at least a part of one or more carbon fibers of said carbon-fiber reinforced composite material.
2. (Withdrawn, Previously amended) The transfer member of Claim 1, wherein the glass fiber epoxy resin layer provides a protective cover for the metal film on the top and bottom surfaces of the body.
3. (Withdrawn, Previously amended) The transfer member of Claim 1, wherein the reflective surface prevents the absorption of thermal energy by a device being transferred by said transfer member.
4. (Previously cancelled).
5. (Withdrawn, Previously amended) The transfer member of Claim 1 or 3, wherein the metal film comprises at least one of titanium, copper, aluminum, steel, gold, silver, nickel, tin, and combinations thereof.
6. (Withdrawn, Previously amended) The transfer member of Claim 1, wherein said carbon-fiber-reinforced composite of said body comprises a non

purity of less than 30 ppm water and less than 5 ppm hydrogen gas being evolved at a vacuum of 10^{-5} Pa, having a temperature condition from 25°C to 250°C at a ramp up rate of 10°C/min.

7. (Withdrawn, Previously amended) The transfer member of Claim 1, wherein said glass fiber epoxy resin comprises a combination of a glass fiber material and an epoxy material.

8. (Withdrawn, Previously amended) The transfer member of Claim 7, wherein said glass fiber material is selected from the group consisting of S-Gss, E-glass, and D-glass.

9. (Withdrawn, Previously amended) The transfer member of Claim 7, wherein said epoxy material comprises condensation products of epichlorohydrin and bisphenol-A.

10. (Withdrawn, Previously amended) The transfer member of Claim 1, wherein said body comprises three layers, each layer having a thickness in the range of from about 0.02 mm to about 1.00 mm.

11. (Withdrawn, Previously presented) The transfer member of Claim 1, wherein at least a portion of said electroconductive polymer part is in direct or indirect contact with a device being transferred by said transfer member.

12. (Withdrawn, Previously presented) The transfer member of Claim 11, wherein said electroconductive polymer part is electrically connected to a grounding conductor by at least a portion of said carbon fibers of said carbon-fiber reinforced composite material.

13. (Withdrawn, Previously presented) The transfer member of Claim 1, wherein said electroconductive polymer part comprises a thermosetting or thermoplastic polymer and an electroconductive filler added thereto.

14. (Withdrawn, Previously presented) The transfer member of Claim 13, wherein said thermosetting or thermoplastic polymer comprises one or more polymers selected from the group consisting of polyimide, fluoropolymer, polyamideimide, polyamide, polyetherimide, polyoxymethylene, polyetheretherketone, polyetherketoneketone, polyetherketone, polyacetate, nylon polymer, aromatic polyimide, polyethersulfone, polyimide polyetherimide, polyester, liquid crystal polymer, polybenzimidazole, poly(paraphenylene benzobisaxazole), polyphenylene sulfide, polycarbonate, polyacrylate, and polyacetal.

15. (Withdrawn, Previously presented) The transfer member of Claim 13, wherein said thermosetting or thermoplastic polymer is polyimide polymer.

16. (Withdrawn, Previously presented) The transfer member of Claim 13, wherein said electroconductive filler comprises one or more materials selected from the group consisting of metal powders, carbon black, carbon fibers, zinc oxide, titanium oxide, and potassium titanate.

17. (Withdrawn, Previously presented) The transfer member of Claim 1, wherein said carbon-fiber reinforced composite material comprises at least one layer of a cloth prepreg containing carbon fibers and at least one layer of a unidirectional prepreg containing carbon fibers, and wherein said body of said transfer member comprises a longitudinal direction with said carbon fibers of said unidirectional prepreg arranged essentially parallel to said longitudinal direction of said body.

18. (Withdrawn, Previously presented) The transfer member of Claim 1, wherein said carbon-fiber reinforced composite material comprises a matrix, said matrix comprising one or more materials selected from the group consisting of a thermosetting polymer, including epoxy, aramid, bismaleimide, phenol, furan, urea, unsaturated polyester, epoxy acrylate, diallyl phthalate, vinyl ester, thermosetting polyimide, and melamine; a thermoplastic polymer, including polyimide resin, nylon, liquid aromatic polyamide, polyester, liquid aromatic polyester, polypropylene, polyether sulfone polymer, polyphenylene sulfide, polyetheretherketone, polyetherketone, polyetherketoneketone, liquid crystal polymer, polysulfone, polyvinylchloride, vinylon, aramid, and fluoropolymer; carbon; a ceramic material, including alumina, silica, titanium carbide, silicon carbide, boron nitride, and silicon nitride; and a metal material, including titanium, aluminum, tin, silicon, copper, iron, magnesium, chromium, nickel, molybdenum, tungsten, and alloys thereof.

19. (Currently Amended) A method of transporting a device ~~which~~ wherein said method prevents radiant thermal energy absorption by a surface of said device, said method comprising transporting said device using ~~the~~ a transfer member ~~of Claim 1~~ comprising;

- a) a body having a carbon-fiber reinforced composite material, said body having a top surface and a bottom surface;
- b) metal films covering the top and bottom surfaces of the carbon-fiber reinforced composite body, said films forming reflective surfaces; and
- c) glass fiber epoxy resin layers covering the sides of the metal films opposite the sides in contact with the carbon-fiber reinforced composite material; and
- d) at least one electroconductive polymer part, wherein said at least one electroconductive polymer part is bonded to said body of step a) and electrically connected to exposed carbon fibers of said carbon-fiber

reinforced composite material of said body of step a) and wherein a portion of said at least one electroconductive polymer part is in contact with said device.

20. (Previously presented) The method of Claim 19 wherein said device is a flat panel display.